

VOMI50 Multi-tube Vortexer 500~2500rpm

Product Details

Product Number

PRO4564



Technical Specification:

Multi-Tube Vortexer is with technique of brushless DC motor and microprocessor-controlled technique. Unique knob operation is easy to use. It can maximum process 50 samples at once. A variety of test tube foams can be selected to meet the mixing needs of different test tubes. It can be widely used in the biotechnology, microbiology, medical analysis and other industries.

Features:

1. Easy to operate with one-touch knob.
2. 1min~99h59min time range, automatic warning sound when finish working.
3. A variety of test tube foam racks for option to meet the mixing needs of different test tubes.
4. Soft start, uniform acceleration, effectively avoid samples splashing.
5. Brushless DC motor: precise shaking speed, long service life maintenance-free.
6. Process up to 50 samples at a time to make the experiment more convenient and efficient.
7. Microprocessor control, simple operation panel, LED displays for speed and time.
8. Humanized program design, built-in short mix and timing operation modes.

Settings	Parameters
Speed range	500~2500rpm
Orbit	4mm
Timing range	1min~99h59min
Max load	4.5kg
Power supply	70W
Voltage	AC110~240V 50/60Hz
Dimension(mm)	410x276x432
Weight	20kg

Accessories:

Type	Foam rack	Test tube
MS200-T10	50x ¢ 10mm	¢ 9~ ¢ 10mm
MS200-T12	50x ¢ 12mm	¢ 11~ ¢ 13mm
MS200-T15	50x ¢ 15mm	¢ 14~ ¢ 17mm
MS200-T20	50x ¢ 20mm	¢ 18~ ¢ 21mm
MS200-T25	15x ¢ 25mm	¢ 24~ ¢ 27mm
MS200-T29	15x ¢ 29mm	¢ 28~ ¢ 32mm