

# VIKING-PHBC – Laboratory Benchtop pH Meter



COLA LabExperts  
[www.colo.si](http://www.colo.si)

# VIKING pH Meters Global Configuration

pH Meter Type	<u>VI</u> <u>KI</u> <u>N</u> <u>G-</u> <u>P</u> <u>H</u> <u>PE</u> <u>C</u>	<u>VIKIN</u> <u>G-</u> <u>PHBA</u>	<u>VIKIN</u> <u>G-</u> <u>PHPO</u> <u>C</u>	<u>VIKIN</u> <u>G-</u> <u>PHCO</u> <u>POC</u>	<u>VIKIN</u> <u>G-</u> <u>PHD</u> <u>OPO</u> <u>C</u>	<u>VIK</u> <u>IN</u> <u>G-</u> <u>PH</u> <u>BC</u>	<u>VIK</u> <u>IN</u> <u>G-</u> <u>PH</u> <u>CO</u> <u>BC</u>	<u>VIK</u> <u>IN</u> <u>G-</u> <u>PH</u> <u>DO</u> <u>BC</u>	<u>VIK</u> <u>IN</u> <u>G-</u> <u>M</u> <u>UB</u> <u>C</u>	<u>VIK</u> <u>IN</u> <u>G-</u> <u>PH</u> <u>BT</u>	<u>VIK</u> <u>IN</u> <u>G-</u> <u>PH</u> <u>CO</u> <u>BT</u>	<u>VIK</u> <u>IN</u> <u>G-</u> <u>PH</u> <u>DO</u> <u>BT</u>	<u>VIK</u> <u>IN</u> <u>G-</u> <u>M</u> <u>UB</u> <u>I</u>	<u>VIK</u> <u>IN</u> <u>G-</u> <u>PH</u> <u>TC</u>	<u>VIK</u> <u>IN</u> <u>G-</u> <u>PH</u> <u>CO</u> <u>TC</u>
pH Type	Pen	Bench	Portabl e	Portabl e	Portabl e	Benc h	Benc h	Benc h	Benc h	Benc h	Benc h	Benc h	Benc h	Table t	Table t
Outdoor Possibility	•	•	•	•	•									•	•
pH Meter	•	•	•	•	•	•	•	•	•	•	•	•	•	•	•
pH/Cond Meter				•			•		•		•		•		•
pH/DO Meter.					•			•				•			
pH/Cond/DO Meter									•				•		
Touch Screen									•	•	•	•	•		
USB Output						•	•	•	•	•	•	•	•	•	•
Bluetooth Option						•	•	•	•	•	•	•	•		
Temperature Sensor			•	•	•					•	•	•	•		
pH composite electrode			•	•	•					•	•	•	•		
Three in One Electrode*						•	•	•	•	•	•	•	•	•	•

\*Electrode: 3-in-1 plastic pH electrode with integrated temperature sensor

## COLO VIKING-PHBC Benchtop pH Meter

- 6.5-inch LCD screen with friendly-use interface
- Automatic calibration, ATC, data storage, clock display, USB output, function settings, wireless printing, and self-diagnosis...
- It supports wireless blue tooth printing. Real-time data transfer to mobile phone via bluetooth is optional.
- Smart electrode status display to ensure accurate use.
- Auto recognition of 25 buffers with three kinds of options: Europe & USA, NIST, Support 1, 2, 3 point calibration with stability indicator, driven by software.

Can store 2000 sets of test data, which can be saved and transferred to USB memory stick and opened with Excel.

3-in-1 plastic electrode with integrated temperature sensor

Type	VIKING-PHBC	
pH	Measurement range	(-2.000 ~ 18.000)pH
	Resolution	0.01 pH
	Accuracy	Electrode : $\pm 0.02$ pH
	Input current	$\leq 2 \times 10^{-12}$ A
	Input impedance	$\geq 1 \times 10^{12}$ $\Omega$
	Stability	$\pm 0.01$ pH/3h
	Temperature compensation	(0 ~ 100) $^{\circ}$ C, auto; (-5 ~ 110) $^{\circ}$ C, auto or manual
mV	Measurement range	(-1999.00 ~ 1999.00) mV
	Resolution	1 mV
	Accuracy	$\pm 0.1\%$ FS
Temperature	Range	(-9,9 ~ 120) $^{\circ}$ C
	Resolution	0.1 $^{\circ}$ C
	Accuracy	$\pm 0.5^{\circ}$ C
Calibration	1, 2, 3 point, auto	
Buffer	Europe & USA, NIST, standards	
Other Parameters	Display	6,5-inch LCD screen
	Data storage	1000 sets
	Power	12 V (110-220, 50-60 Hz adapter)
	Communication interface	USB, RS232, Bluetooth (optional)
	Dimensions&Weight	240×170×70mm/600g
Working Conditions	Temperature	5 ~ 40 $^{\circ}$ C
	Humidity	5-85%
	IP grade	IP54
Meter Kits	pH meter	
	Electrode holder	
	3-in-1 plastic pH electrode with integrated temperature sensor	
	pH buffer solution	
	Power adapter	

Please note

If this pH Meter does not match the specific needs of your application, or some options are not listed for sale, please feel free to contact us. Our manufacturing engineers will come up with technical solutions to meet your needs. We reserve the right to change technical specifications at any time.

## **COLO LabExperts**

Laboratory Equipment Production and Distribution

[www.colo.si](http://www.colo.si)

Presernov Trg 9, 8000 Novo Mesto  
Slovenia

Tel. +386 590 48 880 Email: [office@colo.si](mailto:office@colo.si)